Albertslund Mini Post

Albertslund Mini Post - 5747838666

The fixture emits symmetrical glare-free light directed downwards. The top shade helps direct the light downwards and prevent light from being emitted upwards. The white painted reflectors result in diffuse and comfortable light distribution. The reflector ring protects against direct glare.

Jens Møller-Jensen

Jens Møller-Jensen was born and raised in Copenhagen. In 1955, he finalized his exam as a medical and technical instrument engineer and in 1964, he graduated as an architect from the Royal Danish Academy of Fine Arts, Copenhagen.

Murase Plaza Memorial Park

Product info

Finish

Aluminium coloured with textured surface, graphite with textured surface or grey, powder coated.

Materials

Top shade: Form pressed glass fibre. Enclosure: Injection moulded clear polycarbonate. Heat sink/fixture housing: Die-cast aluminium. Console: Die-cast aluminium. Struts: Stainless steel.

Mounting

Pole dimension: Ø 60mm. Transition pieces for Ø 115mm pole can be bought as accessory parts. Installation cable: 4m, 3x1.5mm2 (Class I) or 4m, 2x1.5mm2 (Class II). Driver: Built into the fixture head.

Sizes and weights

Width x Height x Length (mm) | 660 x 565 x 660 Max 17.4 kg

Class

Ingress protection IP66. Electric shock protection I w. ground, II w/o ground. IK10.

Light source & energy class

LED 3000K 34W

Information

Surge protection device (SPD) not included, but available on request. LED Upgrade kit available for upgrading Albertslund with CFL light sources produced from 2005 and up to previous LED variants. Dimming options CLO, and night time dimming (default setting: 50% power in 8 hours). Available with NEMA and Zhaga socket for Smart City compatibility. Please contact Louis Poulsen for more info about supported Light Management Systems. The driver is integrated in the fixture head.

Product family

Albertslund Wall

Albertslund Maxi Post

Light distribution diagrams

Cartesian

Isolux

Polar

Spare parts & accessories

Product	Variant number
ALB. MINI, POLYC. DIFF. BEFORE 1991	5747291083
ALB. MINI, POLYCARBON. DIFF.	5747291096
ALBERTSLUND MINI SHADE GREY	5747291106
ALB. MINI, DISTANCE TUBE	5747811968
ALB. MINI, INNERSTRUT	5747816633
ALB. MINI, POST ANTI-GLARE SHADE GREY	5747816646
ALB MIN ELASS.150W A65 CLI ORA.SOCK	5747291135
ALB MIN,TRANS.PIECE POLE Ø115/60GREY7005	5747297359
ALB MIN,TRANS.PIECE POLE Ø115/60 GRAPH	5747297362
ALB MIN,TRANS.PIECE POLE Ø115/60 ALUC	5747297375
ALB. MINI, CAP NUT	5747811036
ALB. MINI, REFLECTOR WITH Ø18 HOLE	5747811926
ALB. MINI, LOCK/SUPPORT STRUT	5747811955
ALB. MINI, INC SOCKET	5749320907
ALB. MINI, SOCKET E27	5749321346

Data specifications

BUG Rating	**B1 U3 G1**	Built-in Height	-

Albertslund Mini Post

Class	I
Efficacy	86
IK class	10
IP class	66
L80B10 (hours)	-
Length	660
Lumen	2915
Net Weight	9.707
SDCM	03
Surge Protection. Imax IEC/EN61643-11, V IEC/EN61547	-
Watt	34.0
Wind Load per m2	0.11

CRI	80
Height	565
Inrush Current	-
Kelvin	3000
L80B50 (hours)	-
Light source	LED 3000K 34W
Min. Dim Level (%)	-
Power Factor (P = 100 % / P = 50 %)	-
Standby (W)	-
UGR Transversal / Axial	23.3/23.3
Width	660