


Test report no.: <i>Prüfbericht Nr.:</i>	AU23SW3R 001	Order No.: <i>Auftrags-Nr.:</i>	252105299	Page 1 of 9 Seite 1 von 9
Client Reference No.: <i>Kunden-Referenz-Nr.:</i>	2071295	Order date: <i>Auftragsdatum:</i>	15-Feb-2023	
Client: <i>Auftraggeber:</i>	Aldridge Traffic Systems Pty. Ltd. 12-14 Leeds Street, Rhodes, NSW 2138, Australia			
Test item: <i>Prüfgegenstand:</i>	PLED 40W Street Light			
Identification/ Type No.: <i>Bezeichnung / Typ-Nr.</i>	P40W.N7PAG			
Order content: <i>Auftrags-Inhalt:</i>	Lamp Circuit Power (LCP) Measurement			
Test specification: <i>Prüfgrundlage:</i>	Refer to page 2			
Date of sample receipt: <i>Wareneingangsdatum:</i>	08-Mar-2023			
Test sample No.: <i>Prüfmuster-Nr.:</i>	A003430063-001 to A003430063-010			
Testing period: <i>Prüfzeitraum:</i>	14-Mar-2023 - 15-Mar-2023			
Place of testing: <i>Ort der Prüfung:</i>	TUV Rheinland Australia Pty Ltd			
Testing laboratory: <i>Prüflaboratorium:</i>	TUV Rheinland Australia Pty Ltd			
Test result*: <i>Prüfergebnis*:</i>	Samples were submitted for measurement only, no compliance limits			
tested by: <i>geprüft von:</i>	authorized by: / <i>genehmigt von:</i>			
Date: 21-Mar-2023 <i>Datum:</i>	Qasim Rehan/	Issue Date: 21-Mar-2023 <i>Ausstellungsdatum:</i>	Daniel Ngo/	
Position / Stellung:	Expert	Position / Stellung:	Expert	
Other / <i>Sonstiges:</i>	- Power consumption measurement at rated voltage for AEMO (Australian Energy Market Operator) at lab condition (Ambient (20±5)°C, Relative Humidity (45–75)%).			
Condition of the test item at delivery: <i>Zustand des Prüfgegenstandes bei Anlieferung:</i>	Test item complete and undamaged			
* Legend: P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
* Legende: P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet				
<p>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</p> <p><i>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</i></p>				

Test report no.: AU23SW3R 001

Page 2 of 9
 Seite 2 von 9

Remarks

1	The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.
2	As contractually agreed, this document has been signed digitally only. TÜV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TÜV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged.
3	Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report. Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.
4	The decision rule for statements of conformity in this test report is based on the “Zero Guard Band Rule” and “Simple Acceptance” in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report.
5	This test report is based on assessment and tests applied to the specific test item(s) as submitted by the client. TÜV Rheinland Australia disclaims any and all responsibility or obligation for any other item.
6	LCP test was conducted on 10 fittings as per requested schemes.

History of revision:

N/A

Options/accessories/ancillary equipment:

The equipment was tested without any optional accessory installed. Hence, this report does not cover parameters that are influenced by the installation of optional accessory that might affect safety in the meaning of this standard.

Uncertainty of equipment used:

Equipment	Equipment No.	Range used	Uncertainty	Calibration Due Date
Digital Power Meter	MEL-1400	Voltage: 230V	±0.07V	23-Mar-2023
Model:		Current: 200mA	±0.07mA	
WT210		Power: 0.460W – 4.6kW	±0.2%	
		Power Factor: 1	±0.001pf	

Test procedure:

The submitted test samples (consisted of the supplied lamp and control gear combination, if applicable) for the lamp circuit power consumption measurement were placed in a draught free room and at the laboratory condition (Ambient (20±5)°C, Relative Humidity (45–75)%) for 24 hours before and during the measurement. The test samples were connected to the power source and supplied with voltage and frequency as listed in “TABLE: Power Measurement”. The test samples were operated until the conditions of overall temperature equilibrium were established or at least 4 hours in stabilized operation with the supplied sources. Then the total power consumption measurements have been taken by power meter.

Test report no.: AU23SW3R 001

Page 3 of 9
 Seite 3 von 9

Product description

1	Product details:	LED Street Light Trademark / Manufacturer: Aldridge Traffic Systems Pty. Ltd. Model: P40W.N7PAG Rating: 230Vac; 50Hz; 0.175A; 40W; IP65; IK08; PF>0.9; Class I
2	Dimensions / Weight:	Approx. Length [mm] x Width [mm] x Height [mm]: 570 x 245 x 170 Approx. Weight [kg]: 5.0
3	Operating elements:	Built-in LED driver Trademark / Manufacturer: Inventronics Model: EUM-050S150DG Input rating: 100-240Vac; 50/60Hz; 0.56A; 61W Output rating: +17-54Vdc; 1.5A; 50W ta: -40 °C to +60 °C ; tc: 90°C; IP66/IP67; PF≥0.92
4	Equipment / Accessories:	N/A
5	Used materials:	N/A
6	Other:	Test sample(s), as well sample information, description, product details and intended usage was provided by customer.
7	Test sample obtaining:	<input checked="" type="checkbox"/> Sending by customer <input type="checkbox"/> Sampling by TÜV Rheinland Group <input type="checkbox"/> others:

Test report no.: AU23SW3R 001

Page 4 of 9
 Seite 4 von 9

TABLE: Power Measurement

	Test Item	Supplied Voltage (V)	Frequency (Hz)	Measured Input Power (W)	Measured Input Current (mA)	Power Factor
1	P40W.N7PAG	250.03	50	41.92	172.49	0.9720
2	P40W.N7PAG	250.07	50	41.80	172.07	0.9718
3	P40W.N7PAG	250.08	50	40.50	166.82	0.9708
4	P40W.N7PAG	250.07	50	41.37	170.34	0.9711
5	P40W.N7PAG	250.04	50	41.26	169.77	0.9719
6	P40W.N7PAG	250.09	50	41.73	172.07	0.9698
7	P40W.N7PAG	250.03	50	41.39	170.48	0.9711
8	P40W.N7PAG	250.04	50	41.78	171.75	0.9729
9	P40W.N7PAG	250.03	50	42.62	170.45	0.9708
10	P40W.N7PAG	250.07	50	42.71	170.59	0.9717
	Average	250.06	50	41.708	170.683	0.9714

Test report no.: AU23SW3R 001	Page 5 of 9 Seite 5 von 9
Marking	



Rating label

Test report no.: AU23SW3R 001

Photo documentation



Product overview




Product overview


Photo documentation




LED Panel



Electrical compartment overview



Electrical compartment overview



LED driver

Photo documentation



SPD



Shorting Cap

End of test report